



BBBG2.MH61110 - CAPACITORS, ELECTROCHEMICAL - COMPONENT

Capacitors, Electrochemical - Component

See General Information for Capacitors, Electrochemical - Component

PRC TECH LLC

105 Jordan Rd, Suite 3
Troy, NY 12180 USA

MH61110

Model	Single Capacitor	Capacitor Module	Stationary Use Only	Controlled Environment Temp Limits, °C*	Capacitance, F	Voltage
PR030F(A)	X	—	—	—	30	4.0
PR340F(A)	X	—	—	—	340	4.0
PR375F(A)	X	—	—	—	375	4.0
PR9000F(A)	X	—	—	—	9000	4.0
PR12000F(A)	X	—	—	—	12000	4.0
PR14000F(A)	X	—	—	—	14000	4.0
PR0140F(A)	X	—	—	—	140	4.0
PR0200F(A)	X	—	—	—	200	4.0
PR0800F(A)	X	—	—	—	800	4.0
PR1100F(A)	X	—	—	—	1100	4.0
PR6800F(A)	X	—	—	—	6800	4.0
PR0160 (a)	X	—	—	—	160	4.0
PR0500 (a)	X	—	—	—	500	4.0

* Only applicable to capacitors or capacitor modules for use in "stationary only" applications that are located in controlled environments.

(a) - Followed by additional numbers or letters representing non-safety related identifiers.

Marking: Company name or trademark, model designation and the Recognized Component Mark  .

Last Updated on 2018-11-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.